

EXTENDED REACH TOOLS

Eliminate the hassles of ladders and scaffolding to safely spray hard-to-reach areas like high walls, vaulted ceilings, stairways, and soffits. Complete the job faster with less setup time with a pole gun or the right tip extension length.

POLE GUN

- For unmatched spraying performance in high or recessed areas
- Provides better spray control and less fatigue
- Balanced design with no excessive weight at the end of pole
- Includes CleanShot Shut-Off Valve and Contractor In-Line Valve
- 3600 psi (248 bar, 24.8 MPa)

CLEANSHOT SHUT-OFF VALVE

- Finish faster without resurfacing and touch-ups
- Eliminates spits and drips when using extensions
- Spray walls and ceilings with 180° tip swivel
- Pressure-actuated—operates at a minimum of 700 psi (4.8 MPa, 48 bar)
- 3600 psi (248 bar, 24.8 MPa)

CONTRACTOR IN-LINE VALVE

- Provides a straight connection to extensions for the most optimal rolling position
- In-handle paint filter and built-in swivel connection for top spraying performance
- Ability to rotate 180° allows spraying in any position

POLE GUN EXTENSIONS

- Use with Contractor In-Line valve and the

RAC X AND RAC 5 TIP EXTENSIONS

- Maximum WPR: 4050 psi, (280 bar, 28.0 MPa)
- Includes: RAC X HandTite Guard standard with 7/8 in (22 mm) gun nut and oneseal
- Can be combined for extended reach up to 6 ft (1.8 m)

HEAVY-DUTY EXTENSIONS

- Maximum WPR: 3600 psi (248 bar, 24.8 MPa)
- Can be combined for extended reach up to 12 ft (3.6 m)
- Attach to any airless spray gun or in-line valve
- Ideal for high pressure spraying or low pressure

TELESCOPING EXTENSIONS

- Use telescoping extensions for pressure rolling only—do not use for airless spraying
- All telescoping extensions include adapter
- For use with 7/8 in (22 mm)

180° EASY-TURN DIRECTIONAL SPRAY NOZZLE

- Sprays at a variety of angles by attaching to any Graco extension
- Maximum working pressure: 3600 psi (248 bar, 24.8 MPa)

45° ADAPTER

- Connects to airless spray gun and any Graco extension for use with Pressure Roller or JetRoller
- Maximum working pressure: 3600 psi (248 bar, 24.8 MPa)

EXTENSIONS, SPRAY NOZZLES, AND ADAPTERS

PART #	DESCRIPTION	LENGTH
287023	Pole Gun	3 ft (0.9 mm)
287024	Pole Gun	6 ft (1.8 mm)
287030	Clean-Shot Shut-Off Valve	
244161	Contractor In-Line Valve	
244163	Pole Gun Extensions	3 ft (0.9 mm)
232125	Pole Gun Extensions	6 ft (1.8 mm)
232121	Heavy-Duty Extensions	10 in (25 cm)
232122	Heavy-Duty Extensions	20 in (50 cm)
232123	Heavy-Duty Extensions	40 in (100 cm)
232124	Heavy-Duty Extensions	60 in (150 cm)
232125	Heavy-Duty Extensions	80 in (200 cm)

PART #	DESCRIPTION	LENGTH
287019	RAC X Tip Extension	10 in (25 cm)
287020	RAC X Tip Extension	15 in (38 cm)
287021	RAC X Tip Extension	20 in (50 cm)
287022	RAC X Tip Extension	30 in (75 cm)
243295	RAC 5 Tip Extension	10 in (25 cm)
243296	RAC 5 Tip Extension	15 in (38 cm)
243297	RAC 5 Tip Extension	20 in (50 cm)
243298	RAC 5 Tip Extension	30 in (75 cm)
218775	Telescoping Extensions	18 to 36 in (45 to 90 cm)
218776	Telescoping Extensions	36 to 72 in (90 to 180 cm)
218777	Telescoping Extensions	72 to 144 in (180 to 360 cm)
244825	Telescoping Adapter	
235486	180° Adapter	
224399	45° Adapter	